

omega.x haptic devices

force feedback interfaces



omega.3



omega.6



omega.7

The **omega.x** family of haptic devices relies on a unique kinematic design that has been optimized for high-end force feedback. Its **high mechanical stiffness**, combined with its embedded **USB 2.0 controller**, enables the rendering of **crisp contact forces**.

The **omega.6** and **omega.7** designs provide **perfect decoupling** of translations and rotations. The combination of **full gravity compensation** and **driftless calibration** contributes to greater user comfort and accuracy.

With its unique **active grasping** extension, the **omega.7** is the most versatile haptic device available. Its end-effector covers the **natural range of motion** of the human hand and is compatible with **bi-manual teleoperation** console design.

The **omega.x** family of devices features a modular architecture that makes it possible to **replace one end-effector with another**. Conceived and manufactured in Switzerland, the **omega.x** range is specifically designed for demanding applications where **performance and reliability** are critical, including:

- › medical and space robotics
- › micro and nano manipulators
- › teleoperation consoles
- › virtual simulations
- › training systems
- › research

force dimension

omega.x

workspace	translation	∅ 160 x 110 mm	
	rotation	240 x 140 x 320 180 deg	(omega.6 7)
forces	grasping	25 mm	(omega.7)
	translation	12.0 N	
resolution	grasping	± 8.0 N	(omega.7)
	translation	< 0.01 mm	
	rotation	0.09 deg	(omega.6 7)
	grasping	0.006 mm	(omega.7)

electronics

interface	standard	USB 2.0
	refresh rate	up to 4 KHz
power	universal	110V - 240V

software

platforms	Microsoft	Windows XP / Vista / 7 / 8 Windows CE 7
	Linux	kernel 2.6 / 3.x
	Apple	OS X
	QNX	6.5 / 6.6
	WindRiver	VxWorks 6.3 / 6.8 / 6.9
software	haptic SDK	
	robotic SDK	

features

structure	delta-based parallel kinematics	
	hand-centered rotations	(omega.6 7)
	rotations decoupled from translations	(omega.6 7)
	active gravity compensation	
calibration	automatic	
	driftless	
user input	1 programmable button	
safety	velocity monitoring	
	electromagnetic damping	
option	right- or left-handed	(omega.6 7)

Force Dimension
Route de Saint-Cergue 295
CH - 1260 Nyon
Switzerland

t +41 22 362 6570
f +41 22 362 6571

www.forcedimension.com
info@forcedimension.com